

Laser Line 400V

Product no.: FT91002699N



Benefits

- > The Constant flow control (CFC) guarantees a optimal air flow regulation independent of the filter pollution rate.
- > Efficiency test via USB port
- > Electronic filter control with optical and acoustical filter alarm
- > Laser extraction unit for laser marking, grinding, cutting, welding with high dust amount.



致力于电子测试、维护领域!


For this purpose, we recommend:



Solder fume extractors



Soldering irons



Cleaning



Pre-heating plates



Technical Data

Dimensions L x W x H (mm)	441 x 441 x 1020
Dimensions L x W x H (inches)	17,4 x 17,4 x 40,1
Weight (approx.) in kg	51
Voltage	230 V, 50/60 Hz
Power	460 VA
Noise level (distance 1 m) dB(A)	< 53 dB (A)
Max. vacuum	3000 Pa
Capacity m ³ /h	---
Pre-filter	---
Compact filter	---
Max. capacity	---
RS232 interface (remote control)	All system functions can be operated and remotely monitored via the RS232 port
USB port	The USB port can be used to load firmware updates, run efficiency tests and logdat data.
WX-compatible	---

Owning the bench



PROFESSIONAL

PROFESSIONAL



FILTRATION

FILTRATION



EREM

EREM



XCELITE

XCELITE